

DIGILINK E400 Information Outlet series includes high quality, state-of-the-art face plates for perfect and professional installations needed to provide fully compliant copper cabling systems. DIGILINK E400 information outlets have been engineered to ensure full featured end-to-end connectivity that surpasses Cat 5e requirements. The shutter front access for the cable prevents the entry of dust while the “PERFECT FIT” connector folder design helps easy snapping and removal of the keystone jacks. The cable tie anchor point provides highly effective strain relief for cables.



### Product Features & Compliances

- Available in 1 / 2 / 4 Ports
- Modular design
- Shuttered access
- Exceeds Cat 5e Performance
- Compatible with 22-26 AWG solid cables
- Wall Flush Installation
- Compatible to T568A, T568B wiring pattern
- Fully shielded jack, with metal cover for total EMI/RFI
- UL-94V0 rated plastics
- RoHS Compliant
- ETL Verified
- ANSI/TIA/EIA-568-B.2 Category 5e
- ISO/IEC-11801 (2<sup>nd</sup> edition ) Class D

### Specifications

**Mechanical**

Size: 86 x 86 x 12 mm / 86 x 147 x 12mm  
 Plug retention force: 14Kgf (140N)  
 Plug reliability: 750 cycle minimum  
 Jack Contact Material: Phosphor bronze 50µ” gold over 100µ” nickel plating  
 Conductor compatibility range: 22-26AWG  
 Shield cover: High grade metal cover  
 Standard colour: White

**Electrical**

Current rating: 1.5A max  
 Insulation resistance: 500mΩ (min)@500 Vdc  
 Voltage rating: 72Vdc max  
 Contact resistance: 20mΩ (max) per contact

### Ordering Information

Description	Type	Product Code
DIGILINK Cat 5e+ Information outlet shielded	Single port	DCEIOSMSXXXXX
	Dual port	DCEIODMSXXXXX
	Quad port	DCEIOQMSXXXXX