



Main

Range of product	Actassi
Product or component type	Patch cord
Colour tint	Blue

Complementary

Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Type of cable	4 pair cables
Cable length	1 m
Cable shielding type	FTP
Communication network category	6
Return loss	27 dB
Attenuation	0.1 dB
Near end crosstalk [NEXT]	55.1 dB
Power sum near-end crosstalk [PS NEXT]	52 dB
Far end crosstalk [FEXT]	49.8 dB
Power sum far end crosstalk [PSFEXT]	46.9 dB
Number of matings	1000 cycles
Contact resistance	10 mOhm
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel

Environment

Flame retardance	CM
Standards	IEC 60603-7 ISO/IEC 11801 2nd edition AS/NZS 3080:2003 TIA/EIA-568-B FCC part 68 subpart F

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------